

# Lubricate All Genius Spray

Revision: 17/09/2021

Page 1 from 2

## Technical data

Basis	Mixture of white grease, PTFE and other solid lubricants
Consistency	Liquid
Density	Ca. 0,68 g/ml
Solubility in water	Not soluble
Volatile Organic Compounds (VOC)	76 %
Temperature resistance**	-20 °C → 150 °C
Application temperature	5 °C → 30 °C

\* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. \*\* This information relates to fully cured product.

## Product description

Lubricate All Genius Spray is a high-grade lubricant based on a white grease and PTFE for the treatment of metal and plastic parts. Genius spray allows precise extrusion and regular spray action.

## Properties

- Lubricates
- Reduces friction and wear
- Rust and corrosion-resistant
- Water-repellent
- Does not contain silicones
- For in and outdoor use
- Aerosol can be used in any angle (360°)
- Contains non flammable propellant
- Complies to NSF H1 (Registration No. 156123)

## Applications

- To be used for machines, roller bearings, axles, cogwheels, conveyer belts, rubber gasket profiles,...
- Water resistant and protects against corrosion.
- Foodsafe, may be used in applications where incidental food contact may potentially occur
- Suited for parts which are subject to long or high pressure and temperature loads (-20 to 150°C).

## Packaging

*Colour:* White

*Packaging:* 300 ml aerosol

## Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

## Substrates

*Nature:* clean, free of dust and grease.

All types of metals and plastics.

## Application method

*Application method:* Surfaces must be cleaned, degreased and dry. Shake can well before use. Spray at a distance of appr. 20 cm of the object. To obtain the best result apply the spray while the moving parts are in motion if possible.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.

---

## Lubricate All Genius Spray

---

Revision: 17/09/2021

Page 2 from 2

### Health- and Safety Recommendations

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water. The products mentioned in Annex II of Regulation (EU) 1169/2011 are not part of our formulations and to the best of our knowledge our products do not contain these ingredients.

### Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.